
# 2 Moving Magnet Cartridges





## 2M Moving Magnet Cartridges



#### Advancements in Sound

The 2M Series features Ortofon's trademark split pole pins, an invention which enables moving magnet cartridges to have a flat frequency response as with a moving coil cartridge. Split pole pins were invented by Ortofon, and were originally presented in the 500 and Ortofon OM Series.

The 2M 78, 2M Mono, 2M Red and 2M Blue use an improved engine, which provides an optimized sound reproduction and a high level of sonic accuracy.

The cartridge body used for the 2M Bronze and 2M Black is manufactured from Lexan DMX Piano Black, a revolutionary material which ensures high rigidity while eliminating unwanted resonances.

The 2M Bronze and 2M Black use a special upgraded engine, featuring split pole pins with a silver plated copper wire.





2M Mono / Verso



### Ease of use

The weight and size of 2M Series have been optimized to fit the most common turntables on the market today. The cartridge body has also been streamlined to provide easy mounting and alignment. The name "2M" was chosen as it represents the abbreviation for moving magnet, MM. Moving magnet cartridges provide excellent compatibility in an assortment of playback systems and with a wide variety of phono preamps.

#### Stylus types

All of the 2M cartridges feature diamonds which are polished to the highest standards of the industry. The 2M Red features a tipped Elliptical diamond, while the 2M Blue features a Nude Elliptical diamond.

The 2M Bronze features a Nude Fine Line diamond stylus, which is particularly suited for demanding applications. The



2M Blue / Verso





2M 78 / Verso

2M Red / Verso

erso

2M Bronze / Verso

2M Black / Verso

#### The 2M Series

Ortofon's highly popular 2M series has been expanded with new models: the brand new, true-mono 2M 78 for playback of 78 rpm records, as well as the new 2M Mono for use with mono microgroove recordings.

In addition to the range of acclaimed 2M top-mount models, we are proud to present the new 2M Verso configuration for bottom mounting. Every 2M model is now also available in "Verso" configuration to allow easy mounting on tonearms which do not allow the screws to pass through the top of the headshell. The 2M Series was developed in conjunction with the Danish designer Moeller Jensen Design. Inspired by the facets of a diamond, whose contours gracefully trace the grooves on a record's surface, the 2M's handsome elegance establishes a great combination of form and functionality.

Of course the 2M isn't just another pretty face. It has been engineered to the highest standards and is congruent with Ortofon's unrelenting commitment to providing the most precise and accurate reproduction possible without coloration.

slim profile of the Fine Line stylus will track even the highest frequency information, making it a must for discerning listeners. Additionally, its larger footprint ensures reduced distortion and record wear.

The 2M Black is the moving magnet flagship from Ortofon. The 2M Black is graced with a Nude Shibata diamond stylus – the same diamond as on the acclaimed MC Cadenza Black. Its slim, highly polished profile allows an exceedingly wide contact area to the groove walls and ensures notably detailed reproduction throughout the spectrum, including even the most high frequency groove information. Users of the 2M Black will enjoy the benefit of impeccable sound quality, along with reduced record & stylus wear and reduced distortion and phase error as a result of the diamond's improved tracking geometry.

The 2M 78 features a 65 µm Spherical stylus that is perfect for playback of 78 rpm records, which require a larger stylus profile for proper playback.

The 2M Mono Features a 18 µm Nude Spherical stylus that is an optimal solution for playing mono microgroove vinyl records. Both 2M Mono and 2M 78 feature an optimized engine for superior sound quality and use a strapped output to deliver the same output signal from both sets of pole pins. This effectively eliminates the need for mono-specific equipment, making it easily possible to enjoy true mono reproduction on any stereo playback system.

#### 2M Plug-and-Play

The 2M PnP cartridges are available premounted on our exclusive 2M series headshell for easy attachment to most bayonet-style, removable headshell tonearms.

The 2M PnP is a practical and elegant solution which adds unique distinction to your turntable.













2M 78 PnP

2M Mono PnP

2M Red PnP

2M Blue PnP

2M Bronze PnP

2M Black PnP

## 2MMoving Magnet Cartridges



TECHNICAL DATA

Output voltage at 1 kHz, 5cm/sec. Channel balance at 1 kHz Channel separation at 1 kHz Channel separation at 15 kHz Frequency range at -3 dB Frequency response

Tracking ability at 315 Hz at recommended tracking force Compliance, dynamic, lateral Stylus type Stylus tip radius Tracking force range Tracking force, recommended Tracking angle Internal Impedance, DC resistance Internal inductance Recommended load resistance Recommended load capacitance Cartridge colour, body/stylus Cartridge weight without screws Replacement stylus unit

#### 2M 78 / Verso

4 mV

20-20,000 Hz 20-20,000 Hz +3/-1 dB

70 µm 18 µm/mN Spherical R 65 µm 1.6-2.0 g(16-20 mN) 1.8 g (18 mN) 20° 0.7 kOhm 300 mH 47 kOhm 150-300 pF Black/Grey 7.2 g 2M 78

### 2M Mono / Verso

4 mV 20-22,000 Hz

20-20.000 Hz +3/-1 dB 70 µm

18 µm/mN Nude Spherical R 18 µm 1.6-2.0 g(16-20 mN) 1.8 g (18 mN) 20° 0.7 kOhm 350 mH 47 kOhm 150-300 pF Black/White 7.2 g 2M Mono

2M Red / Verso 5.5 mV 1.5 dB 22 dB 15 dB 20-22,000 Hz 20-20.000 Hz +3/-1 dB

70 µm 20 µm/mN Elliptical r/R 8/18 µm 1.6-2.0 g(16-20 mN) 1.8 g(18 mN) 20 1.3 kOhm 700 mH 47 kOhm 150-300 pF Black/Red 7.2 g 2M Red

2M Blue / Verso 5.5 mV 1.5 dB 25 dB 15 dB 20-25,000 Hz 20-20.000 Hz +2/-1 dB

80 µm 20 µm/mN Nude Elliptical r/R 8/18 µm 1.6-2.0 g(16-20 mN) 1.8 g(18 mN) 20° 1.3 kOhm 700 mH 47 kOhm 150-300 pF Black/Blue 7.2 g

2M Blue

2M Bronze / Verso 5 mV 1 dB 26 dB 15 dB 20-29,000 Hz 20-20.000 Hz

+2/-0 dB

22 µm/mN

80 µm

20°

1.2 kOhm

630 mH

47 kOhm

7.2 g

150-300 pF

2M Bronze

15 dB 20-31,000 Hz 20-20,000 Hz +2/-0 dB 80 µm 22 µm/mN Nude Shibata r/R 6/50 µm

5 mV

1 dB

26 dB

2M Black / Verso

Nude Fine Line r/R 8/40 µm 1.4-1.7 g(14-17 mN) 1.4-1.7 g(14-17 mN) 1.5 g (15 mN) 1.5 g (15 mN) 20 1.2 kOhm 630 mH 47 kOhm 150-300 pF Black/Bronze Black/Black 7.2 g

> ortofon accuracy in sound

2M Black